

R-DRK paper collated nails with fuel cells

Ring shank bright nails for timber framing, roofing and other timber applications



Certificate



Product information

Features and benefits

- 34° angle collation with a clipped head ensures the nail is compatible with all leading manufactures tools
- Special coating at the base of the shank improves the drive of the nail and ensures a secure fixing
- Diamond point prevents the timber from splitting
- Waxed paper collation avoids deterioration in wet conditions
- Paper tape collation ensures that no collating material is left on the work site
- Depending on the quantity of nails box contains 1,2 or 3 fuel cells
- A wide variety of combinations of nail coatings and finishes allows everyone to find the right solution for a particular application

Corresponding products

- R-RAWL-WW90CH Gas powered framing nailer

Applications

- Timber frame stud work in timber framing industry
- Manufacturing of timber standardised structure like Timber frame houses or roof elements
- Installation of battens and sheathing in roof construction
- Installation of soffits and other roof finishing elements
- Installation of wooden facades
- Installation of timber flooring and terraces

Base materials

- Timber
- Chipboard
- Plywood
- Wood

Attention

- Nail packs without the fuel cells are available for use with pneumatic and cordless tools



Technical Data

Index	Fastener diameter	Length	Head type	Shank type	Finish	Protection	Collation	Fasteners per	Carton quantity	Fuel cells per	Box weight	Outer weight	EAN
	[mm]	[mm]						[pcs]	[pcs]	[pcs]	kg	kg	
R-DRK-2851	2.8	51	Clipped head	Ring	Bright	Minimum 10m	34° paper laminated	44	3300	3	9.26	9.26	5906675 047539
R-DRK-2863	2.8	63	Clipped head	Ring	Bright	Minimum 10m	34° paper laminated	44	3300	3	11.15	11.15	5906675 049786
R-DRK-3163	3.1	63	Clipped head	Ring	Bright	Minimum 10m	34° paper laminated	44	3300	3	13.34	13.34	5906675 070964
R-DRK-2870	2.8	70	Clipped head	Ring	Bright	Minimum 10m	34° paper laminated	44	3300	3	12.09	12.09	5906675 266756
R-DRK-2875	2.8	70	Clipped head	Ring	Bright	Minimum 10m	34° paper laminated	44	3300	3	12.98	12.98	5906675 070988
R-DRK-3175	3.1	75	Clipped head	Ring	Bright	Minimum 10m	34° paper laminated	44	2200	2	10.33	10.33	5906675 038377
R-DRK-3190	3.1	90	Clipped head	Ring	Bright	Minimum 10m	34° paper laminated	44	2200	2	12.27	12.27	5906675 225692